

HOOKLIFTS



MULTILIFT

UP TO 40% LIGHTER

More Legal Payload = Increased Profits

UP TO 60% FASTER

Faster Turnaround (*Ultima Performance Package*) = Increased Profits

LOWEST MOUNTING HEIGHT

Lowest Center of Gravity = Best Load Handling Stability

UNMATCHED SAFETY FOCUS

Hook Safety Latch • Body Up Warning System • Maintenance Prop...



12,000 lb. to 72,000 lb. Capacities ■ Class 5 - 8 Chassis ■ 10' to 24' Container Lengths ■ Nationwide Service & Support

BUILT TO PERFORM



MULTILIFT

MODEL	MAX. CAPACITY (LB)	OPTIMUM BODY LENGTHS (FT)	MAX. TIPPING ANGLE (°)	HOOK HEIGHT (IN)	CA / CT RANGE (IN)	MIN. GVWR (LB)	FRAME HEIGHT (IN)	CLEAR FRAME (IN)	WEIGHT (LB)
XR5S-3050	12,000	10 - 12	50	36	84 - 96	19,500	UP TO 38	138	1,345
XR5S-3250	12,000	11 - 13	50	36	102 - 110	19,500	UP TO 38	148	1,480
XR8S-3250	18,000	11 - 13	50	36 / 54	102 - 110	22,000	UP TO 40	144	2,160
XR8S-3650	18,000	12 - 14	50	36 / 54	114 - 122	22,000	UP TO 40	158	2,225
XR8S-4150	18,000	14 - 16	50	36 / 54	132 - 140	22,000	UP TO 40	176	2,290
XR10S-3250	22,000	11 - 13	50	54	102 - 110	33,000	UP TO 43	146	2,180
XR10S-3650	22,000	12 - 14	50	54 / 62	116 - 124	33,000	UP TO 43	160	2,290
XR10S-4150	22,000	14 - 16	50	54 / 62	134 - 142	33,000	UP TO 43	178	2,360
XR10S-5100	22,000	17 - 19	50	54 / 62	174 - 182	33,000	UP TO 43	218	2,535
OPT15S-4300	30,000	14 - 16	50	54 / 62	152 CA / 130 CT	35,000	UP TO 44	188	3,585
OPT15S-4600	30,000	15 - 17	50	54 / 62	162 CA / 140 CT	35,000	UP TO 44	198	3,650
OPT15S-5600	30,000	18 - 20	50	54 / 62	200 CA / 176 CT	35,000	UP TO 44	236	4,100
ULT16S-4600	40,000	15 - 17	50	54 / 62	130 - 140	50,000	UP TO 45	198	3,830
ULT16S-5300	40,000	18 - 20	50	54 / 62	164 - 174	50,000	UP TO 45	228	4,225
ULT18S-5900	40,000	20 - 22	50	54 / 62	180 - 190	50,000	UP TO 45	248	4,455
ULT21S-5300 (PF)	50,000	18 - 20	50	54 / 62	166 - 176	60,000	UP TO 45	236	5,435
ULT21S-5900 (PF)	50,000	20 - 22	50	54 / 62	184 - 194	60,000	UP TO 45	252	5,565
ULT26S-5300 (PF)	60,000	18 - 20	50	54 / 62	166 - 176	70,000	UP TO 45	236	5,845
ULT26S-5900 (PF)	60,000	20 - 22	50	54 / 62	184 - 194	70,000	UP TO 45	252	6,020
ULT30S-5900 (PF)	72,000	20 - 22	50	62	184 - 194	80,000	UP TO 45	252	6,270

Tarp Installation - Remember to add 12" to the CA / CT and Clear Frame measurements listed above for best weight distribution. Basic sales drawings for each hooklift model are available upon request (intended for illustration purposes only). Custom weight distributions may also be requested (allow 2-3 weeks). **PF** = performance package available. The performance package is optional, consists of fast tipping (25 sec.), fast lowering (30 sec.), fast off-load (35 sec.) and auto sequence (one touch loading and unloading).

STANDARD PRODUCT FEATURES	XR SERIES	OPT SERIES	ULT SERIES
Electric Cab Control	X	X	X
High Tensile Steel Construction	X	X	X
Dual Pivot Design (true dumping)	X	X	X
Hook Safety Latch	X	X	X
Body Up Warning Light	X	X	X
Sensors / Wiring - IP67	X	X	X
Zinc Primer / Top-Coat Black	X	X	X
Proportional PLC Controller (smart system)			X
Soft Lowering (dump cycle)		X	X
Friction Relief (loading / unloading)			X
Float Function (rough road assist)		X	X
Pull Limiter (manage short bodies)		X	X
Solid Cast Inserts (critical stress points)		X	X
Product Warranty (all parts / structural)	2-yr / 3-yr	2-yr / 3-yr	2-yr / 5-yr

