TECHNICAL SPECIFICATIONS T-HIDUO 038






BUILT TO PERFORM

HIAB T-HIDUO 038 BASIC DATA

TECHNICAL DATA	T-DUO 038-2	T-DUO 038-3	T-HIDUO 038-3	T-HIDUO 038-4
Max. lifting capacity (ft-lbs)	28 760	30 980	30 980	30 980
Outreach, hydraulic extensions (ft)	12' 0"	15' 11"	15' 11"	19' 10"
Outreach / lifting capacity (ft-lbs)	4' 11" - 5 200 8' 2" - 3 090 11' 10" - 2 140 - -	5' 3" - 4 850 8' 6" - 2 910 12' 2" - 2 010 15' 9" - 1 540 -	5' 3" - 4 850 8' 6" - 2 910 12' 2" - 2 010 15' 9" - 1 540 -	5' 7" - 4 500 8' 10" - 2 730 12' 6" - 1 900 16' 1" - 1 460 19' 8" - 1 190
Slewing angle (°)	190 - 330	190 - 330	190 - 330	190 - 330
Height in folded position (in)	70	70	70	70
Width in folded position (in)	44	44	44	44
Installation space needed (in)	22	22	22	22
Weight, "standard" crane without stabilizers (lbs)	680	770	770	860



19'8

1190

15'9

1540

2910

2010

bs

4850

A Duo crane is manually operated and easy to use, but it automatically adds a higher level of safety. The crane's SPACE system provides automatic assistance, making it easier to operate the crane safely without special training. Plus it tracks the crane's usage, providing valuable statistics and indicating when service and repairs are needed.

597-4016/1

▎**▋▕▆▁▎**╕**▕▕▋▎▆┥**╶╴ years ahead for paint quality and protection

Hiab's nDurance[™] paint is an anti-corrosion paint system using nano technology for the ultimate anti-corrosion coating, maintaining a rust-free reliable crane.

Hiab ProCare[™] is a proactive preventative maintenance service contract, designed to maximize uptime of all Hiab equipment by maintaining proper service intervals.

Hiab's Leading Warranty exceeds the industry's standard terms because our products are designed to last longer and provide many years of reliable service.

truck mounted forklifts and tail lifts. We aim to set the industry benchmark for ci

Hiab USA Inc 12233 Williams Road Perrysburg, OH 43551 USA tel. +419 482 6000 fax. +419 482 6001

2910 2010



hiab.us.com