



CRANE MAY BE DERATED IN REAR QUADRANTS AS MUCH AS 30%. ACTUAL DERATING SHALL BE BASED ON PHYSICAL TESTING.

TRUCK, HIAB CRANE & ACCESSORIES WEIGHT DISTRIBUTION, NO PAYLOAD, LIFT AXLE UP.	
TOTAL WEIGHT ON FRONT AXLE	= 14,680 LBS.
TOTAL WEIGHT ON TANDEM AXLE	= 28,500 LBS.
FRONT AXLE WT. PERCENTAGE	= 34 %
TANDEM AXLE WT. PERCENTAGE	= 66 %
GROSS VEHICLE WEIGHT	= 43,180 LBS.

TRUCK, HIAB CRANE & ACCESSORIES WEIGHT DISTRIBUTION, WITH PAYLOAD, LIFT AXLE DOWN.	
TOTAL WEIGHT ON FRONT AXLE	= 18,660 LBS.
TOTAL WEIGHT ON TANDEM AXLE	= 31,500 LBS.
TOTAL WEIGHT ON LIFT AXLE	= 11,000 LBS.
FRONT AXLE WT. PERCENTAGE	= 31 %
TANDEM AXLE WT. PERCENTAGE	= 51 %
LIFT AXLE WT. PERCENTAGE	= 18 %
GROSS VEHICLE WEIGHT	= 61,160 LBS.
WATER WEIGHT PAYLOAD	= 17,980 LBS.

TRUCK SPECIFICATIONS	
TRUCK MODEL	= FREIGHTLINER 114SD SFA
WHEELBASE	= 289"
CAB TO TANDEM	= 205 1/2"
AXLE-TO-FRAME	= 144"
FRONT AXLE CURB WEIGHT	= 10,246 LBS.
REAR AXLE CURB WEIGHT	= 9,576 LBS.
FRONT G.A.W.R.	= 20,000 LBS.
REAR G.A.W.R.	= 46,000 LBS.
YIELD STRENGTH OF EACH FRAME RAIL	MINIMUM SECTION MODULUS REQUIRED
120,000 P.S.I. YIELD	= 38.44 in. ³
MINIMUM RBM/RAIL OF 4,613,070 IN-LBS	

NOTES:
 DOUBLE FRAME CHASSIS REQUIRED.
 FRAME RAIL MUST MEET OR EXCEED THE MINIMUM RBM REQUIRED.
 FULL LENGTH SUBFRAME REQUIRED:
 6"x4"x1/2" RECT. TUBING (ON TOP OF CHASSIS FRAME)
 5"x5"x3/8" RECT. TUBING (CROSSMEMBERS EVERY 3 FT.)
 3/8" TOP PLATE & 1/4" BOTTOM PLATE REQUIRED - FULL LENGTH
 CURB WEIGHTS WERE PROVIDED WITHOUT TAG INSTALLED.
 BODY WEIGHTS WERE ESTIMATED.

TRUCK RUNS IN US (RULES FOR MOST STATES).
 20,000 LBS. ALLOWED ON FRONT AXLE.
 34,000 LBS. ALLOWED ON TANDEM.
 42,500 LBS. ALLOWED ON TRIDEM (9').
 62,500 LBS. ALLOWED FOR GROSS WEIGHT (31').
 MAXIMUM LENGTH CANNOT EXCEED 40.'

NOTICE:
 THE DRAWING PURPOSE IS TO INTRODUCE A GENERAL CONCEPT OF A PROPOSED IDEA.

NOTICE:
 THIS WEIGHT DISTRIBUTION IS BASED ON ESTIMATED WEIGHTS AND IS ONLY AS ACCURATE AS THOSE ESTIMATES. ACTUAL WEIGHTS MAY CHANGE THE RESULTS OF THIS WEIGHT DISTRIBUTION.

Hiab, Inc.
 Hiab, Inc.
 12233 Williams Road
 Perryburg, Ohio 43551
 Tel (419) 482-6000
 Fax (419) 482-6001
 Tolerances - unless otherwise noted.
 Tolerances are in inches
 2-PLACE ±.00..... .03
 3-PLACE ±.000..... .015
 ANGULAR ± 1'
 FRACTIONAL ± 1/16"
 Break all sharp corners unless otherwise specified.

THIS PROPERTY AND ALL INFORMATION THEREIN IS THE PROPERTY OF HIAB, INC., 12233 WILLIAMS RD, PERRYBURG, OHIO 43551 AND IS CONFIDENTIAL. IT MUST NOT BE MADE PUBLIC OR COPIED. THIS DRAWING IS LOANED TO RETURN UPON DEMAND AND SHALL NOT BE USED DIRECTLY OR INDIRECTLY IN ANY WAY DETRIMENTAL TO OUR INTERESTS. OUR PRIOR SPECIFIC APPROVAL IS REQUIRED FOR EXPOSURE OF THIS DRAWING TO OTHERS FOR ANY PURPOSE.
 Next Assy.
 Dwg/Cad file no. 425K / SALES

Drawing Title:		HIAB 425K-4 HIPRO	
Project Name:		SALES LAYOUT	
Drawn by:	Date:	Size:	Part No.
CSV	2-6-19		
Approval:	Date Approved:	Scale:	unit wt.
			Eng. job no.: