



GALFAB



OX SERIES **SHORT EXTENDIBLE TAIL HOIST**

The Short Extendible Tail roll-off hoist has a 40" tail extension in lieu of the 80" extension which allows for this model to come standard with the GALFAB Auto-Fold DOT bumper. This hoist allows for low loading height for limited overhead clearance as well as the ability to pick up below ground level. This hoist is also available in the 8" mainframe and 2" subframe and the 10" sub frameless hoist.

Combines the versatility of an outside rail hoist with the flexibility of an extendable tail.



Visit our website: GALFAB.com | Follow us on social media



| Call Today: 574-946-7767

THE GALFAB **ADVANTAGE**



Outboard Supported Side Rollers

Greasable Roller shaft is removable with two bolts for ease of replacement and maintenance.



Low Loading Angle

An 80" tail provides a low loading angle.



Auto Fold Bumper

Bumper folds forward reducing the chance of bending and hang-ups in the landfill.



Visit our website: GALFAB.com | Follow us on social media



| Call Today: 574-946-7767

STANDARD FEATURES

- 8" x 4 x 3/8" Main Frame Tube
- 1/2 inch x 3 1/2 inch Wear Strip on Top
- 3" x 2" x 1/4" Subframe
- 2 1/2" Diameter Rear Hinge
- All Working Points Greaseable
- Pintle Ready Apron
- 1" Spring Loaded Container Locks
- 2 1/2" Diameter Lift Cylinder Shafts
- Interchangeable 10 " Vertical and Horizontal Sheaves
- 3/8 inch x 3-inch Winch Cylinder Rod Covers
- 6 Inboard and Outboard Supported Outside Rollers
- 48 Gallon Oil Reservoir with Sight and Temperature Gauge
- 25 Micron Filtration

- Inside and Outside Controls
- Choice of Forward or Reverse Mount Single-Stage or Telescopic Lift Cylinders
- LED Lighting System
- 7/8" Cable with Heavy Duty Swivel Eye Hook
- 40-inch Extendible Tail
- GALFAB Auto-fold DOT Bumper
- Front Mount Pump
- Hoist Up Warning Light
- Sealed Wiring System
- Hoist Up Alarm
- Backup Alarm

OPTIONAL FEATURES

- Behind Cab and Oversize Oil Tanks
- Tool Boxes
- Auxilliary Stops
- Poly or Steel Fenders
- Aluminum Fenders
- Tarping Systems
- Hooker Hold On Systems
- Ratchet Tie Down Straps

- Integrated hydraulics can be used, if hydraulic tarping system is used
- PTO
- Drop Shaft
- Rear View Camera Systems
- Work Lights
- Onboard Scale Systems



**"The Hooker"
Container
Securement System**



**Auxillary fold down
stops**



Hydraulic Reservoirs



Tool Boxes



**Poly, Steel &
Aluminum Fenders**

Shop all replacement parts at:

GALFAB.com



Visit our website: [GALFAB.com](https://www.galfab.com) | Follow us on social media



| Call Today: 574-946-7767

OX SERIES MODELS

Model	Capacity	CA	CA with tarp	Length	Dump Angle Tail Retracted	Dump Angle Tail Extended	Up (sec)*	Down (sec)*	On (sec)*	Off (sec)*	Lift Cylinder	Winch Cylinder	Container Length ft	Apx Weight lbs
OX60174S072	60,000	174"	186"	23'3"	48°	28°	27	15	41	28	6" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7,550
OX60174S072R	60,000	174"	186"	23'3"	48°	28°	27	15	41	28	6" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7,550
OX60174T121	60,000	174"	186"	23'3"	48°	28°	35	29	41	28	6"-5"-4" x 121" DAT	7" x 4" x 79.5" DA	18'-22'	7,225
OX75174S072F7	75,000	174"	186"	23'3"	48°	28°	37	23	41	28	7" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7,550
OX75174S072R7	75,000	174"	186"	23'3"	48°	28°	37	23	41	28	7" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7,550
OX75174T121	75,000	174"	186"	23'3"	48°	28°	35	29	41	28	6"-5"-4" x 121" DAT	7" x 4" x 79.5" DA	18'-22'	7,350
OX60194S072	60,000	194"	206"	24'11"	48°	28°	27	15	46	31	6" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7,850
OX60194S072R	60,000	194"	206"	24'11"	48°	28°	27	15	46	31	6" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7,850
OX60194T121	60,000	194"	206"	24'11"	48°	28°	35	29	46	31	6"-5"-4" x 121" DAT	7" x 4" x 89.5" DA	20'-24'	8,075
OX75194S072F7	75,000	194"	206"	24'11"	48°	28°	37	23	46	31	7" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7,850
OX75194S072R7	75,000	194"	206"	24'11"	48°	28°	37	23	46	31	7" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7,850
OX75194T121	75,000	194"	206"	24'11"	48°	28°	35	29	46	31	6"-5"-4" x 121" DAT	7" x 4" x 89.5" DA	20'-24'	8,075

* Cycle Times are Factory developed and controlled by PTO output, oil viscosity, human and mechanical efficiency, and may vary accordingly.

CAUTION: This Equipment Should be Operated by Properly Trained Personnel. Improper Use, Misuse, or Lack of Maintenance Could Cause Injury to Persons or Property. Photos used in this brochure are illustrative only. We reserve the right to make changes at any time without notice. Information contained within this literature is believed to be the most accurate available at the time of printing.

